

# X210

Special Carbon black

Introduction to the:

炭黑 X210 专为各种密封剂、粘合剂等提供优异的分散性、蓝相性、增强性、防紫外线、防静电等。

Carbon black X210 Designed for all kinds of sealants, adhesives, etc. Provides excellent dispersion, blue phase, reinforcement, UV protection, anti - static and so on.

应用与特性 PROPERTIES:

项 目 system	参 数	
	最小值 MINIMUM	最大值 MAXIMUM
外观 PHYSICAL FORM	粉状 POWDER	
平均原生粒径(nm) AVERAGE ORIGINAL PARTICAL SIZE (nm)	28	32
吸碘值 IAN ABSORBING IODINE VALUE	118	125
比表面积m <sup>2</sup> /g SPECIFIC SURFACE AREA	115	125
DBP 吸收值 cc/100g DBP OIL ABSORPTION (cc/100g)	108	118
相对着色力, IRB3=100% TINT STRENGTH VS IRB#3 (%)	110	118
密度 (g/l) DENSITY (g/l)		
PH 值 PH VALUE	8.0	8.5

- ◆ 优秀的分散性 Excellent dispersion
- ◆ 蓝相 Blue phase
- ◆ 紫外线防护/UV protection
- ◆ 补强性推荐应用 Reinforcement recommend application:
- ◆ 各类密封剂、粘结剂 All kinds of sealants, adhesives
- ◆ 包装 packaging: 10KG/Bag

工厂地址: 新疆生产建设兵团第七师五五工业园区工业大道 18 号

address: No. 18, Industrial Avenue, 5th industrial park, 7th division, Xinxiang production and construction corps

销售地址: 深圳市宝安区 松岗街道 佳裕大厦 1803

address: 1803 Jiayu Building, Songgang Street, Bao'an District, Shenzhen city, China.

电话 The phone: +86 (0) 755 23246611; 13510821649 传真 fax: +86 (0) 755 29467129

邮箱 Email: texong@163.com

网址 The url: www.texong.com