

BP128

Special Carbon black

Introduction to the:

炭黑 BP128 专为各种 PP\PET 纤维制品、PU 密封剂、粘合剂等提供优异分散性、蓝相性、中高等黑度等。

Carbon black BP128 is specially designed to provide excellent dispersion, blue phase, medium blackness for various PP(PET) fiber products, PU sealants, adhesives, etc.

应用与特性 PROPERTIES:

项 目 system	参 数	
	最小值 MINIMUM	最大值 MAXIMUM
外观 PHYSICAL FORM	粒状/粉状 POWDER	
平均原生粒径(nm) AVERAGE ORIGINAL PARTICAL SIZE (nm)	22	26
吸碘值 IAN ABSORBING IODINE VALUE	115	125
比表面积m ² /g SPECIFIC SURFACE AREA	110	120
DBP 吸收值 cc/100g DBP OIL ABSORPTION (cc/100g)	112	117
相对着色力, IRB3=100% TINT STRENGTH VS IRB#3 (%)	106	110
密度 (g/l) DENSITY (g/l)		
PH 值 PH VALUE	8.0	8.0

- ◆ 优秀的分散性 Excellent dispersion
- ◆ 蓝相 Blue phase
- ◆ 中等黑度/ Medium blackness
- ◆ 各类密封剂、纤维制品 All kinds of sealants, Fiber products
- ◆ 包装 packaging: 20KG/Bag

工厂地址: 新疆生产建设兵团第七师五五工业园区工业大道 18 号

address: No. 18, Industrial Avenue, 5th industrial park, 7th division, Xinxiang production and construction corps

销售地址: 深圳市宝安区松岗街道 佳裕大厦 1803

address: 1803 Jiayu Building, Songgang Street, Bao'an District, Shenzhen city, China.

电话 The phone: +86 (0) 755 23246611; 13510821649 传真 fax: +86 (0) 755 29467129

邮箱 Email: texong@163.com

网址 The url: www.texong.com