

EnBlack XA1000

特种炭黑 Special carbon black

简介 introduction:

特种炭黑 EnBlack XA1000 设计用于塑料、涂料、油墨、墨汁、陶瓷等，是一种通用型粉末状颜料黑，具有分散性好、深度蓝相、高流动性、着色力高、应用广等特点。Special carbon black EnBlack XA1000 is designed for plastic, paint, ink, ink, ceramics, etc. It is a universal powder pigment black with good dispersion, deep blue phase, high fluidity, high coloring power, and wide application.

理化指标 Physical and Chemical Indicators:

理化性质 Physical and Chemical Properties	参数 parameter
外观 Appearance	粉末 powder
平均原生粒径 Average primary particle size (nm)	24±1
BET 比表面积 BET Specific surface area (m ² /g)	150±10
DBP 吸油值 DBP Oil Absorption (cc/100g)	45±5
相对着色, Tinting strength IRB#3(%)	130±5
挥发份 Volatile matter (%)	0.2±1
PH 值	2.5±0.5

应用与特性 Application and characteristics:

- ◆ 高分散 High dispersion
- ◆ 蓝相 Blue phase
- ◆ 高流动性 High fluidity
- ◆ 高着色力 High tinting strength

推荐应用 Recommended application:

用于塑料、涂料、油墨、墨汁

For plastics, paint, ink, ink

包装 packing: 20KG/Bag

备注: 本数据资料的提供出于诚意, 仅供参考, 需要由您自己测试并决定是否适合您的用途, 对我们产品的应用和处理以及您制造的最终产品都处于我们的控制之外, 我们无法承担保证和义务。

PS:The Data above is provided in good faith,FYI.

工厂地址: 新疆胡杨河市胡杨经济技术开发区车排子西路 3 号

公司地址: 东莞市常平镇桥沥南北路 25 号 电话: +86 (0) 755 23246611; 13510821649

邮箱: texong@163.com

网址: www.texong.com